



Specifications

OS	Windows plug & play
INTERFACE	USB HID and USB KB
CONNECTION	USB Type A plug, 6ft
CURRENT & POWER	Power via USB 100 mA max USB: 5V
STATUS INDICATORS	Status LED (Green)
MSR/SCRA SWIPES	1 Million
DIMENSIONS	3.92 (L) x 1.24 (W) x 1.2 (H) in.
WEIGHT	1.8 oz. (50 gr) without cable
MOUNT/STABILIZER	Screws or fastening tape
MAGSTRIPE	Triple Track (TK1/2/3); Bidirectional read; ISO 7811, 4 ips to 60 ips
ENVIRONMENTAL	<p><u>Operating Temperature:</u> 32°F to 158°F (0°C to 70°C)</p> <p><u>Storage Temperature:</u> -40°F to 158°F (-40°C to 70°C)</p> <p><u>Non-condensing Operating and Storage Humidity:</u> 10% to 90%</p>
SECURITY	Data protection 3DES encryption; DUKPT key management MagneSafe Security Architecture Unique, non-changeable device serial number
CERTIFICATE	Compliance (FCC, CE, UL),
TAMPER	Evident/Resistant



Main Features



USB Type A



Swipe



3DES
Encryption



FCC, CE, UL

Additional Information

User Manual & Setup Guide [↗](#)

Shop MagTek Dynamag [↗](#)

V.022025