



## Specifications

<b>OS</b>	Windows plug & play
<b>INTERFACE</b>	USB HID, USB KB, and MSR Emulation
<b>CONNECTION</b>	USB
<b>CURRENT &amp; POWER</b>	Power via USB
<b>MTBF</b>	<u>Electronics</u> : 125,000 hours <u>Head</u> : 1,000,000 passes
<b>CARD SPEED</b>	3 to 50 IPS
<b>DIMENSIONS</b>	3.94 (L) x 1.28 (W) x 1.23 (H) in.
<b>WEIGHT</b>	Reader with cable: 5.8 oz. (1,65g)
<b>RECORDING</b>	Two-frequency coherent phase (F2F)
<b>MAGSTRIPE</b>	Triple Track (TK1/2/3); Bidirectional read; ISO 7811, 3 ips to 50 ips
<b>ENVIRONMENTAL</b>	<u>Temperature</u> : Operating: 32°F to 131°F (0°C to 55°C) Storage: -22°F to 158°F (-30°C to 70°C) <u>Humidity</u> : Operating: 10% to 90% noncondensing Storage: Up to 100% noncondensing <u>Altitude</u> : Operating: 0-10,000 ft. (0-3,048m) Storage: 0-50,000 ft. (0-15,240m)
<b>STANDARDS</b>	ISO, ANSI, CDL and AAMVA



### Main Features

- USB
- Bi-directional Swipe
- ISO, ANSI, CDL and AAMVA Compatible
- Triple Track

### Additional Information

- User Manual & Setup Guide [↗](#)
- Shop MagTek Magstripe Mini [↗](#)

V.022025