









## Specifications



<b>DISPLAY</b>	2.8" QVGA, Color LCD
<b>AUDIO</b>	<u>Default:</u> Buzzer <u>V200c Plus:</u> Audio Speaker
<b>USER INTERFACE</b>	4-way Navigation button + (2) selection keys   Backlit Keypad   Tactile 15 Key Keypad
<b>PRINTER</b>	30 Ips   40mm Paper Roll
<b>CARD READERS</b>	<u>Triple track MSR:</u> ISO 7810, 7811, 7813; <u>Smart Card Reader:</u> EMVCo-approved
<b>COMMUNICATIONS</b>	<u>Default:</u> Dial-up, Ethernet <u>V200c Plus:</u> 5 GHz + 2.4 GHz WiFi, Bluetooth 4.2 BLE
<b>CONTACTLESS</b>	ISO 14443 Types A and B, ISO 18092-capable, EMVCo L1 certification, MIFARE, supports major NFC/CTLS schemes
<b>MEMORY</b>	<u>Default:</u> 128MB RAM + 256MB Flash <u>V200c Plus:</u> 512MB RAM + 512MB Flash, Micro SD
<b>OS</b>	V/OS (Linux-based)
<b>PROCESSOR</b>	600 MHz, Arm Cortex-A9 32-bit RISC, 1500 MIPS
<b>SECURITY</b>	PCI PTS 5.X-approved
<b>POWER</b>	<u>AC input:</u> 100-240 VAC, 50/60 Hz; <u>DC output:</u> 11.6 V 1.55 A
<b>DIMENSIONS</b>	190 (L) × 80 (W) × 70 (H) mm <u>Weight:</u> 381g
<b>PORTS</b>	(2) USB connectors: (1) host, (1) host/client; (1) RS-232-powered
<b>ENVIRONMENTAL</b>	<u>Operating Temperature:</u> 0° to 50° C (32° to 122° F), <u>Storage Temperature:</u> -20° to 60° C (-4° to 140° F), <u>Relative Humidity, Non-condensing:</u> 5% to 90%



### Main Features

-  Ethernet, Wi-Fi & Bluetooth
-  Chip, Swipe, + Contactless
-  ARM Cortex A9
-  512MB RAM + 512MB Flash
-  2.8" LCD Screen Size
-  40mm Thermal Printer

### Additional Information

- User Manual & Setup Guide 
- Shop Verifone V200c Plus 

V.032025