



Specifications

DISPLAY	3.5" HVGA color, capacitive touchscreen, Corning® Gorilla® Glass technology
MEMORY	384 MB (256 MB Flash, 128 MB SDRAM), microSD
PROCESSOR	600 MHz, 1500 MIPS, Arm Cortex-A9 32-bit RISC
CARD READERS	Triple track MSR: ISO 7810, 7811, 7813; smart card reader: EMVCo-approved
OS	V/OS (Linux-based)
CONTACTLESS	ISO 14443 Types A and B, ISO 18092-capable, EMVCo L1 certification, MIFARE, supports major NFC/CTLS schemes
CONNECTIVITY	USB, RS232, Ethernet
DIMENSIONS	167 (L) × 80 (W) × 44 (H) mm <u>Weight:</u> 310 g
AUDIO	Speaker
ACCESSORIES	Mounting adapter, power over Ethernet (POE 802.3af), cables backward compatible with VX
POWER SUPPLY	5-12 V DC, 4.8-5.2 W power consumption, power over USB 5 V 500 mA
ENVIRONMENTAL	<u>Operating Temperature:</u> 0° to 50° C (32° to 122° F); <u>Storage Temperature:</u> -20° to 60° C (-4° to 140° F); <u>Relative Humidity, Non-Condensing:</u> 5% to 90%,
SECURITY	PCI PTS 5.X-approved



Main Features

- Wi-Fi or Bluetooth
- Chip, Swipe, + Contactless
- Arm Cortex-A9 32-bit RISC
- 256 MB Flash + 128 MB SDRAM
- 3.5" LCD Touchscreen
- PCI PTS 5.x

Additional Information

- User Manual & Setup Guide [🔗](#)
- Shop Verifone P400 [🔗](#)

V.032025